



safety for your pipeworks

# SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/8

Printing date: 12.03.2018  
Trade name: GIRPI RERFIX

Revision: 28.02.2018  
Version number: 16

## 1 / Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name: **GIRPI RERFIX** (RERFIXP / RERFIXB)

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture: Adhesive

### 1.3 Details of the supplier of the safety data sheet

#### Manufacturer(1)/Supplier(2):

2

GIRPI

Rue Robert Ancel

CS 90133

76700 HARFLEUR / FRANCE

Tel.: 33(0)2 32 79 60 00

Fax: 33(0)2 32 79 60 27

E-mail: [contact@girpi.fr](mailto:contact@girpi.fr)

Further information obtainable from: Technical Assistance

Tel: 33(0)2 32 79 58 00

1.4 Emergency telephone number: INRS

Tel: 33(0)1 45 42 59 59

## \* 2 / Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

#### Hazard pictograms



GHS02



GHS07

Signal word Danger

#### Hazard-determining components of labelling:

methyl ethyl ketone

#### Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

#### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.



safety for your pipeworks

# SAFETY DATA SHEET

Page 2/8

according to 1907/2006/EC, Article 31

Printing date: 12.03.2018  
Trade name: GIRPI RERFIX

Revision: 28.02.2018  
Version number: 16

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing vapours.
- P370+P378 In case of fire: Use to extinguish: Water haze, Alcohol resistant foam, Fire-extinguishing powder, Carbon dioxide.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with national regulations.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

**==>> Labelling of packages where the contents do not exceed 125 ml**

**Hazard pictograms**



GHS02



GHS07

**Signal word** Danger

**Hazard-determining components of labelling:**

methyl ethyl ketone

**Hazard statements**

H336 May cause drowsiness or dizziness.

**Precautionary statements**

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P261 Avoid breathing vapours.
- P501 Dispose of contents/container in accordance with national regulations.

**2.3 Other hazards**

**Results of PBT and vPvB assessment**

- PBT:** Not applicable.
- vPvB:** Not applicable.

## 3 / Composition/information on ingredients

**3.2 Mixtures**

**Description:** Adhesive

<b>. Dangerous components:</b>		
CAS: 646-06-0 EINECS: 211-463-5 Reg.nr.: 01-2119490744-29	1,3-dioxolane Flam. Liq. 2, H225;  Eye Irrit. 2, H319	50-100%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43	methyl ethyl ketone Flam. Liq. 2, H225;  Eye Irrit. 2, H319; STOT SE 3, H336	25-50%
CAS: 128-37-0 EINECS: 204-881-4 Reg.nr.: 01-2119565113-46	2,6-di-tert-butyl-p-cresol Aquatic Acute 1, H400; Aquatic Chronic 1, H410	<1%

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

## 4 / First aid measures

**4.1 Description of first aid measures**

- General information:** No special measures required.
- After inhalation:** Supply fresh air; consult doctor in case of complaints.
- After skin contact:** Generally the product does not irritate the skin.



safety for your pipeworks

## SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 3/8

Printing date: 12.03.2018  
Trade name: GIRPI RERFIX

Revision: 28.02.2018  
Version number: 16

---

### . After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

### . After swallowing:

Do not induce vomiting; call for medical help immediately.

### . 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

### . 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

---

## 5 / Firefighting measures

### . 5.1 Extinguishing media

#### . Suitable extinguishing agents:

- Water haze
- Alcohol resistant foam
- Fire-extinguishing powder
- Carbon dioxide

#### . For safety reasons unsuitable extinguishing agents:

Water with full jet

### . 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

### . 5.3 Advice for firefighters

#### . Protective equipment:

Mount respiratory protective device.

#### . Additional information

Cool endangered receptacles with water spray.  
Collect contaminated fire fighting water separately. It must not enter the sewage system.

---

## 6 / Accidental release measures

### . 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

### . 6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/ surface or ground water.

### . 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

### . 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

---

## 7 / Handling and storage

### . 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

### . Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

### . 7.2 Conditions for safe storage, including any incompatibilities

#### . Storage:

#### . Requirements to be met by storerooms and receptacles:

Store in a cool location.

#### . Information about storage in one common storage facility:

Not required.

#### . Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

### . 7.3 Specific end use(s)

No further relevant information available.



safety for your pipeworks

## SAFETY DATA SHEET

Page 4/8

according to 1907/2006/EC, Article 31

Printing date: 12.03.2018  
Trade name: GIRPI RERFIX

Revision: 28.02.2018  
Version number: 16

### \* 8 / Exposure controls/personal protection

. **Additional information about design of technical facilities:** No further data; see item 7.

#### . 8.1 Control parameters

. <b>Ingredients with limit values that require monitoring at the workplace:</b>	
<b>78-93-3 methyl ethyl ketone</b>	
WEL (Great Britain)	Short-term value: 899 mg/m <sup>3</sup> , 300 ppm Long-term value: 600 mg/m <sup>3</sup> , 200 ppm Sk, BMGV
IOELV (European Union)	Short-term value: 900 mg/m <sup>3</sup> , 300 ppm Long-term value: 600 mg/m <sup>3</sup> , 200 ppm
. <b>Ingredients with biological limit values:</b>	
<b>78-93-3 methyl ethyl ketone</b>	
BMGV (Great Britain)	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one

. **Additional information:** The lists valid during the making were used as basis.

#### . 8.2 Exposure controls

##### . **Personal protective equipment:**

##### . **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

##### . **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

##### . **Recommended filter device for short term use:** Filter A

##### . **Protection of hands:**

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

##### . **Material of gloves**

Butyl rubber, BR

Recommended thickness of the material: > 0,7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

##### . **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

##### . **Eye protection:**



Tightly sealed goggles

##### . **Body protection:** Solvent resistant protective clothing



safety for your pipeworks

## SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 5/8

Printing date: 12.03.2018  
Trade name: GIRPI RERFIX

Revision: 28.02.2018  
Version number: 16

### 9 / Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

##### General Information

##### Appearance:

Form:	Fluid
Colour:	Light orange colour
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	75 °C
Flash point:	-6 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	274 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.8 Vol %
Upper:	11.5 Vol %
Vapour pressure at 20 °C:	133 hPa
Density at 20 °C:	1.042 g/cm <sup>3</sup>
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Organic solvents:	26.8 %
Water:	0.0 %

##### 9.2 Other information

All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

### 10 / Stability and reactivity

10.1 Reactivity No further relevant information available.

#### 10.2 Chemical stability

##### Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.



safety for your pipeworks

## SAFETY DATA SHEET

Page 6/8

according to 1907/2006/EC, Article 31

Printing date: 12.03.2018  
Trade name: GIRPI RERFIX

Revision: 28.02.2018  
Version number: 16

### 11 / Toxicological information

#### . 11.1 Information on toxicological effects

. **Acute toxicity** Based on available data, the classification criteria are not met.

. LD/LC50 values relevant for classification:		
<b>646-06-0 1,3-dioxolane</b>		
Oral	LD50	3,000 mg/kg (rat)
Dermal	LD50	8,480 mg/kg (rbt)
Inhalative	LC50/4 h	20.65 mg/l (rat)
<b>78-93-3 methyl ethyl ketone</b>		
Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rbt)
<b>128-37-0 2,6-di-tert-butyl-p-cresol</b>		
Oral	LD50	890 mg/kg (rat)

. **Primary irritant effect:**

. **Skin corrosion/irritation** Based on available data, the classification criteria are not met.

. **Serious eye damage/irritation**

Causes serious eye irritation.

. **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

. **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

. **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

. **Carcinogenicity** Based on available data, the classification criteria are not met.

. **Reproductive toxicity** Based on available data, the classification criteria are not met.

. **STOT-single exposure**

May cause drowsiness or dizziness.

. **STOT-repeated exposure** Based on available data, the classification criteria are not met.

. **Aspiration hazard** Based on available data, the classification criteria are not met.

### 12 / Ecological information

#### . 12.1 Toxicity

. **Aquatic toxicity:** No further relevant information available.

. **12.2 Persistence and degradability** No further relevant information available.

. **12.3 Bioaccumulative potential** No further relevant information available.

. **12.4 Mobility in soil** No further relevant information available.

. **Additional ecological information:**

. **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

. **12.5 Results of PBT and vPvB assessment**

. **PBT:** Not applicable.

. **vPvB:** Not applicable.

. **12.6 Other adverse effects** No further relevant information available.

### 13 / Disposal considerations

. **13.1 Waste treatment methods**

. **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

. **Uncleaned packaging:**

. **Recommendation:**

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.



safety for your pipeworks

## SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 7/8

Printing date: 12.03.2018  
Trade name: GIRPI RERFIX

Revision: 28.02.2018  
Version number: 16

### 14 / Transport information

- . **14.1 UN-Number**
- . **ADR/ADN, IMDG, IATA**
- . **14.2 UN proper shipping name**
- . **ADR/ADN**
- . **IMDG, IATA**
- . **14.3 Transport hazard class(es)**
- . **ADR/ADN**

UN1133

1133 ADHESIVES  
ADHESIVES



- . **Class**
- . **Label**
- . **IMDG, IATA**

3 (F1) Flammable liquids.  
3



- . **Class**
- . **Label**
- . **14.4 Packing group**
- . **ADR/ADN, IMDG, IATA**
- . **14.5 Environmental hazards:**
- . **Marine pollutant:**
- . **14.6 Special precautions for user**
- . **Danger code (Kemler):**
- . **EMS Number:**
- . **Stowage Category**

3 Flammable liquids.  
3

III

No

Warning: Flammable liquids.

33

F-E,S-D

A

- . **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

- . **Transport/Additional information:**
- . **ADR/ADN**

- . **Limited quantities (LQ)**
- . **Excepted quantities (EQ)**

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

3

D/E

- . **Transport category**
- . **Tunnel restriction code**

- . **IMDG**
- . **Limited quantities (LQ)**
- . **Excepted quantities (EQ)**

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

- . **Remarks:**

Under certain conditions substances in Class 3 (flammable liquids) can be classified in packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2

- . **UN "Model Regulation":**

UN 1133 ADHESIVES, 3, III



safety for your pipeworks

## SAFETY DATA SHEET

Page 8/8

according to 1907/2006/EC, Article 31

Printing date: 12.03.2018  
Trade name: GIRPI RERFIX

Revision: 28.02.2018  
Version number: 16

### 15 / Regulatory information

- . **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- . **Directive 2012/18/EU**
- . **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- . **Seveso category** P5c FLAMMABLE LIQUIDS
- . **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- . **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- . **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 40
- . **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### \* 16 / Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### . **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

#### . **Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

. **Department issuing SDS:** Technical Assistance                      Tel: 33(0)2 32 79 58 00

#### . **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

. \* **Data compared to the previous version altered.**